

Quick start

Installation

To install Quality API, simply run the following command in your Next.js project's root folder:

npm:

```
npm install @quality-api/core
```

Yarn:

```
yarn add @quality-api/core
```

pnpm:

```
pnpm install @quality-api/core
```

... And that's it! You're now all good to go.

Your first endpoint and middleware

When building endpoints with Quality API, you're using the [builder pattern](#), which is common in languages like [Rust](#).

Each middleware is defined in chronological order, meaning the middleware defined first, is executed first when calling the endpoint, naturally.

Here is an example of an endpoint fetching a list of users with filters via URL search parameters, using Zod.

```
import QualityApi from "@quality-api/core";
import Db from "@db";
import z from "zod".
```

```

const searchParamsSchema = z.object({
  searchText: z.string().optional().default(null)
});

const validateSearchParams = QualityApi.createMiddleware(async r => {
  const parseResult = await searchParamsSchema.safeParseAsync(r.body);

  if (parseResult.success) {
    return r.transformBody(parseResult.data);
  }
  else {
    return Response.json({ error: "Invalid search params" }, { status: 400 });
  }
});

export const GET =
  QualityApi.initBuilder()
    .mw(validateSearchParams)
    .handle(request => {

      const users = await Db.query(`
        SELECT *
        FROM users
        WHERE $1 IS NULL OR $1 IN name
      `, [request.url.searchParams.searchText])

      return Response.json(users);
    });

```

In this example, the request's search params are validated before the request is handled.

When using `request.url.searchParams`, it's correctly type-annotated to the Zod schema.

Usually, it's recommended separating middleware and schemas into separate files, but this is all up to you - naturally, it does not affect the usability.

Revision #5

Created 2026-08-05 23:41:35 UTC by Lars Kvihaugen

Updated 2026-08-06 00:14:01 UTC by Lars Kvihaugen